

University of Denver

## Digital Commons @ DU

---

Electrical and Computer Engineering: Graduate  
Student Scholarship

Department of Electrical and Computer  
Engineering

---

2015

# Using Robots as Therapeutic Agents to Teach Children with Autism Recognize Facial Expression

Seyedmohammad Mavadati

University of Denver, mavadati.mohammad@gmail.com

Huanghao Feng

University of Denver, howard.k.feng@gmail.com

Peyten B. Sanger

University of Denver

S. Silver

University of Denver

Anibal Gutierrez

Florida International University

Follow this and additional works at: [https://digitalcommons.du.edu/ritchie\\_ece\\_gstudent\\_scholarship](https://digitalcommons.du.edu/ritchie_ece_gstudent_scholarship)



Part of the [Cognition and Perception Commons](#), [Electrical and Computer Engineering Commons](#), and the [Robotics Commons](#)

---

### Recommended Citation

Mavadati, Seyedmohammad; Feng, Huanghao; Sanger, Peyton B.; Silver, S.; Gutierrez, Anibal; and Mahoor, Mohammad H., "Using Robots as Therapeutic Agents to Teach Children with Autism Recognize Facial Expression" (2015). *Electrical and Computer Engineering: Graduate Student Scholarship*. 5.

[https://digitalcommons.du.edu/ritchie\\_ece\\_gstudent\\_scholarship/5](https://digitalcommons.du.edu/ritchie_ece_gstudent_scholarship/5)



This work is licensed under a [Creative Commons Attribution 4.0 License](#).

This Conference Abstract is brought to you for free and open access by the Department of Electrical and Computer Engineering at Digital Commons @ DU. It has been accepted for inclusion in Electrical and Computer Engineering: Graduate Student Scholarship by an authorized administrator of Digital Commons @ DU. For more information, please contact [jennifer.cox@du.edu](mailto:jennifer.cox@du.edu), [dig-commons@du.edu](mailto:dig-commons@du.edu).

---

## Using Robots as Therapeutic Agents to Teach Children with Autism Recognize Facial Expression

### Comments

Abstract of a paper presented at the International Meeting for Autism Research, May 13-16, 2015 - Salt Lake City, UT, USA.

Full conference proceedings may be found at: <https://insar.confex.com/imfar/2015/webprogram/start.html>

### Authors

Syedmohammad Mavadati, Huanghao Feng, Peyton B. Sanger, S. Silver, Anibal Gutierrez, and Mohammad H. Mahoor

**Title:** Using Robots as Therapeutic Agents to Teach Children with Autism Recognize Facial Expression

**Background:** Recognizing and mimicking facial expressions are important cues for building great rapport and relationship in human-human communication. Individuals with Autism Spectrum Disorder (ASD) have often deficits in recognizing and mimicking social cues, such as facial expressions. In the last decade several studies have shown that individuals with ASD have superior engagement toward objects and particularly robots (i.e. humanoid and non-humanoid). However, majority of the studies have focused on investigating robot’s appearances and the engineering design concepts and very few research have been done on the effectiveness of robots in therapeutic and treatment applications. In fact, the critical question that “*how robots can help individuals with autism to practice and learn some social communicational skills and applied them in their daily interactions*” have not been addressed yet.

**Objective:** In a multidisciplinary research study we have explored how robot-based therapeutic sessions can be effective and to some extent they can improve the social-experiences of children with ASD. We developed and executed a robot-based multi-session therapeutic protocol which consists of three phases (i.e. baseline, Intervention and human-validation sessions) that can serve as a treatment mechanism for individuals with ASD.

**Methods:** We recruited seven (2F/5M) children 6-13 years old (Mean=10.14 years), diagnosed with High Functioning Autism (HFA). We employed NAO, an autonomous programmable humanoid robot, to interact with children in a series of social games for several sessions. We captured all the visual and audio communications between NAO and the child using multiple cameras. All the capturing devices were connected to a monitoring system outside of the study room, where a coder observed and annotated the responses of the child online. In every session, NAO asked the child to identify the type of prototypic facial expression (i.e. happy, sad, angry, and neutral) shown on five different photos. In the ‘*baseline*’ sessions we calculated the prior knowledge of every child about the emotion and facial expression concepts. In the ‘*intervention*’ sessions, NAO provides some verbal feedback (if needed), to help the child identify the facial expression. After finishing the intervention sessions, we included two ‘*human-validation*’ sessions (with no feedback) to evaluate how well the child can apply the learned concepts when a human is replaced with NAO.

**Results:** The following Table demonstrates the mean and Standard Deviation (STD) of face recognition rates for all subjects in three phases of our study. In our experiment six out of seven subjects had baseline recognition rate lower than 80% and we observed high variation (STD) between different subjects.

| Facial Expression Recognition Rate (%) | Baseline             | Intervention         | Human-Validation     |
|--|----------------------|----------------------|----------------------|
| Mean (STD)                             | <b>69.52</b> (36.28) | <b>85.83</b> (20.54) | <b>94.28</b> (15.11) |

**Conclusions:** The results demonstrate the effectiveness of NAO for teaching and improving facial expression recognition (FER) skills by children with ASD. More specifically, in the *baseline*, the low FER rate (69.52%) with high variability (STD=36.28) demonstrate that overall, participants had difficulty recognizing expressions. The statistical results of *intervention* phase, confirms that NAO can teach children recognizing facial expressions reliably (higher accuracy with lower STD). Interestingly, in the *human-validation* phase children could even recognize the basic facial expressions with a higher accuracy (94%) and very limited variability (STD = 15.11). These results conclude that robot-based feedback and intervention with a customized protocol can improve the learning capabilities and social skills of children with ASD.